

# T.ORD

When years of experience build “excellent accesories”




## PRESENTATION

Stainless steel rotary sprayer diffuser, specifically developed in order to be applied in the remounting of red wines, where from the top of the vinification tank it can distribute the must all over the “hat”, improving the polifenolic extraction and consequently the color point of the red wines.

Excellent the application combined with a TC.DV pump, where the right quantity of flow assures a correct management of the process.

## APPLICATIONS



Winery

## TECNICAL DATA

<b>Connections</b>	DIN 11851 (standard), Tri-clamp, SMS, GAS, ENO-GAROLLA, RJT	<b>Flow</b>	Depending on the system
<b>Impeller</b>	Daisy flower, 4 blades	<b>Head</b>	-
<b>Pump case material</b>	AISI 316 (1.4401), AISI 304 (1.4301), for estruded or laminated components	<b>Maximum pressure on the inlet pipeline</b>	-
<b>Mechanical seal and gaskets</b>	Internal single execution	<b>Temperature</b>	Between -20°C e +240°C Other outer range temperatures on request
<b>Frame</b>	Monobloc, with axial ball bearings	<b>Viscosity</b>	Up to 50 cP For clean liquids. For specific applications, the usage limits with suspended solids are indicated on the pump technical data sheet
<b>Motor</b>	1ph, 17W, 24Vac	<b>Suspended solids</b>	

[www.tecnicapompe.it](http://www.tecnicapompe.it)